

MINIATURE OPEN BEVEL GEARBOX UNIT. PART NO: 919D35





DIMENSIONS	d	L	L1	L2	L3	D	R	H	H1	H2	d1
Millimeter	5	50	15	32	19.4	4.8	6	10	18.8	4	12

This unit has particularly useful applications in situations where dust and debris are absent, in-line configuration is not pos sible and accessibility is a premium design consideration. It consists of a robust diecast zinc chassis/frame housing, 5mm dia steel C45 shafts and POM/Acetal self-lubricating gears at 1:1 ratio. A generous length of input shaft is provided allowing for a variety of driv e motors to be considered. A triangular mounting hole configuration offers strength and stability in operation.

Polyketone gear version is available (Providing high resistant chemical/abrasion properties).

1:1 gear ratio **Lubricated for life** **Designed for rugged service life**

SPECIFICATION: **Weight:** **60g** **Torque:** **846 g.cm**

IN-LINE COUPLINGS



5 - 5mm **Part No. 919D1/5**

5 - 6mm **Part No. 919D1/3**

1 Llwyn Bleddyn, Llanllechid, Bangor, LL57 3EF, UK
TEL: 01304 612132
EMAIL: info@mfacomo.com
WEB: www.mfacomodrills.com

THE ABOVE FIGURES ARE A GUIDE ONLY AND DO NOT FORM ANY CONTRACTUAL OBLIGATION ON THE PART OF MFA/COMO DRILLS.